

**Table 38g**

**Dimensions for Spiral Wound Gasket Applications  
To ASME B16.20 for use with metric bolts – Class 1500lb**

Dimensions in millimetres

Nominal Bore		Centering Ring O/D	Sealing Element O/D	Sealing Element I/D	Inner Ring I/D	Nominal Bore
Inches	Metric					
1/2	15	62.5	31.8	19.1	14.2	1/2
3/4	20	69	39.6	25.4	20.6	3/4
1	25	77.5	47.8	31.8	26.9	1
1 1/4	32	87	60.5	39.6	33.3	1 1/4
1 1/2	25	97	69.9	47.8	41.4	1 1/2
2	50	141	85.9	58.7	52.3	2
2 1/2	65	163.5	98.6	69.9	63.5	2 1/2
3	80	173	120.7	92.2	78.7	3
4	100	209.5	149.4	117.6	97.8	4
5	125	253	177.8	143	124.5	5
6	150	281.5	209.6	171.5	147.3	6
8	200	351.5	257.3	215.9	196.9	8
10	250	434.5	311.2	266.7	246.1	10
12	300	519.5	368.3	323.9	292.1	12
14	350	579	400.1	362	320.8	14
16	400	641	457.2	406.4	368.3	16
18	450	702.5	520.7	463.6	425.5	18
20	500	756	571.5	514.4	476.3	20
24	600	900.5	679.5	616	577.9	24

**Dimensional data supplied by customer and to be used as reference only**