

Table 62**ASME B16.47 Series B Flanges (Formerly API 605)**

NOMINAL BORE	CLASS 75		CLASS 150		CLASS 300		CLASS 400		CLASS 600	
	O/D	I/D	O/D	I/D	O/D	I/D	O/D	I/D	O/D	I/D
26	708.0	660.0	725.0	660.0	772.0	660.0	746.0	660.0	765.0	660.0
28	759.0	711.0	776.0	711.0	826.0	711.0	800.0	711.0	819.0	711.0
30	810.0	762.0	827.0	762.0	886.0	762.0	857.0	762.0	879.0	762.0
32	860.0	813.0	881.0	813.0	940.0	813.0	911.0	813.0	933.0	813.0
34	911.0	864.0	935.0	864.0	994.0	864.0	962.0	864.0	997.0	864.0
36	973.0	914.0	987.0	914.0	1048.0	914.0	1022.0	914.0	1048.0	914.0
38	1024.0	965.0	1045.0	965.0	1099.0	965.0	-	-	-	-
40	1075.0	1016.0	1095.0	1016.0	1149.0	1016.0	-	-	-	-
42	1126.0	1067.0	1146.0	1067.0	1200.0	1067.0	-	-	-	-
44	1181.0	1118.0	1197.0	1118.0	1251.0	1118.0	-	-	-	-
46	1232.0	1168.0	1256.0	1168.0	1318.0	1168.0	-	-	-	-
48	1283.0	1219.0	1307.0	1219.0	1368.0	1219.0	-	-	-	-
50	1334.0	1270.0	1357.0	1270.0	1419.0	1270.0	-	-	-	-
52	1387.0	1321.0	1408.0	1321.0	1470.0	1321.0	-	-	-	-
54	1438.0	1372.0	1464.0	1372.0	1530.0	1372.0	-	-	-	-
56	1495.0	1422.0	1514.0	1422.0	1594.0	1422.0	-	-	-	-
58	1546.0	1473.0	1580.0	1473.0	1656.0	1473.0	-	-	-	-
60	1597.0	1524.0	1630.0	1524.0	1705.0	1524.0	-	-	-	-

Dimensions in millimetres