

Table 87**Jacketed Gasket Dimensions to suit ASME B16.47 Series B Flanges**

Flange Size NPS	Gasket Inside Diameter	GASKET OUTSIDE DIAMETER BY CLASS				
		150	300	400	600	900
26"	673.1	722.4	768.4	743.0	762.0	835.2
28"	723.9	773.2	822.5	797.1	816.1	898.7
30"	774.7	824.0	882.7	854.2	876.3	955.8
32"	825.5	877.8	936.8	908.1	930.4	1013.0
34"	876.3	931.9	990.6	958.9	993.9	1070.1
36"	927.1	984.3	1044.7	1019.3	1044.7	1120.9
38"	977.9	1041.4	1095.5	1070.1	1101.9	1197.1
40"	1028.7	1092.2	1146.3	1124.0	1152.7	1247.9
42"	1079.5	1143.0	1197.1	1174.8	1216.2	1298.7
44"	1130.3	1193.8	1247.9	1228.9	1267.0	1365.3
46"	1181.1	1252.5	1314.5	1286.0	1324.1	1432.1
48"	1231.9	1303.3	1365.3	1343.2	1387.6	1482.9
50"	1282.7	1354.1	1416.1	1400.3	1444.8	-
52"	1333.5	1404.9	1466.9	1451.1	1495.6	-
54"	1384.3	1460.5	1527.3	1514.6	1552.7	-
56"	1435.1	1511.3	1590.8	1565.4	1603.5	-
58"	1485.9	1576.3	1652.5	1616.2	1660.7	-
60"	1536.7	1627.1	1703.3	1679.7	1730.5	-

Dimensions in millimetres

Tolerances:

Outside Diameter (mm) (NPS 26" 60")	Inside Diameter (mm) (NPS 26" 60")	Thickness (mm) (NPS 26" 60")
+ 3.30 mm / - 0	+ 3.30 mm / - 0	+ 0.8 / - 0